

Tri-Blade

Features

- ✓ 2.75m or 4.0m cutting widths
- ✓ 3.0m transport width
- ✓ Variable cutting height
- ✓ Three sets of timed blades
- ✓ Slip clutch protection
- ✓ Front and rear heavy duty chain guards
- ✓ Cat II three point linkage
- ✓ 1000 rpm gearbox driven



The Tri-blade mowers are heavy duty and robust.

Three Sets of newly designed heavy duty timed blades ensure strip free cutting, with an adjustable cutting height of between 25mm (1") and 225mm (9") the Bomford Tri-Blade range offers superb versatility.

Driven through 1000 rpm independent gearbox's with rubber pto shaft couplings to offer further protection against debris impact the tri-blade delivers power direct to the blades.

Slip clutch protection on each pto shaft ensures longevity of the independent gearbox's.

	Tri-Blade 3000	Tri-Blade 4000
Cutting width	2.75m (9')	4.0m (13'2")
Transport width	3.0m (9'10")	1.8m (6')
Length	3.54m (11'4")	4.54m
Weight	1130kg	1325kg
Cutting height	25mm - 225mm (1" - 10")	25mm - 225mm (1" - 10")
PTO input	1000 rpm	1000 rpm
Power requirement	90hp	120hp

