

AW TRAILERS

Low Loader Trailers

There are two types of Low Loader Trailers available :-

Standard Low Loader Trailer



The standard Low Loader Trailer has a flat bed with a single axle at the rear which is hydraulically operated so that the bed can be lowered to the ground for easy loading and then raised for travelling. This trailer is designed to transport agricultural implements such as power harrows and drill combinations.

Plant Low Loader Trailer



This has tandem axles under a flat bed with a beaver tail and fold down ramps at the rear for easy loading. It is designed to carry wheeled or tracked plant and equipment including diggers and excavators.

Standard Low Loader Trailer



Optional extras available include :-

- Hardwood Floor
- Drawbar Skid
- Steering Axle

Standard features include :-

- Hydraulic Brakes
- LED Full Road Lighting
- Rope Hooks
- Heavy Duty Heat Treated Hitch Eye
- Choice of Steel Tread Plate or Softwood Floor



5 Tonne

6 Tonne

7 Tonne

	5 Tonne	14ft	6 Tonne	18ft	7 Tonne	21ft
Body length	4270mm	14ft	5485mm	18ft	6400mm	21ft
Body width	2500mm	8ft 2"	2500mm	8ft 2"	2500mm	8ft 2"
Chassis	150 x 75 PFC		180 x 75 PFC		200 x 75 PFC	
Axle (single)	70mm 6 stud		70mm 6 stud	80mm 8 stud	80mm 8 stud	
Brake size	300 x 60mm		300 x 60mm	350 x 60mm	350 x 60mm	
Tyre size	12.5/80 x 15.3 14 ply		12.5/80 x 15.3 14 ply	385/65R22.5 'super single'	385/65R22.5 'super single'	
Wheel track	2000mm		2000mm		2000mm	
Lifting rams	2		2		2	
o/a length	6585mm	21ft 8"	7900mm	25ft 11"	9100mm	29ft 10"
o/a width	2500mm	8ft 2"	2500mm	8ft 2"	2500mm	8ft 2"

AW Engineering (Hereford) Ltd.
Stoney Street
Madley
Hereford
HR2 9NQ

Tel : 01981 251558
Fax : 01981 251568

Web : www.awtrailers.co.uk
Email : sales@awtrailers.co.uk

Plant Low Loader Trailer



Standard Low Loader Trailer Features :-

- 6mm Steel Tread Plate Floor
- Spring Assisted Loading Ramps
- 18" high Fixed Headboard
- Hydraulic Brakes
- Full Road Lighting
- Commercial Ratchet type Park Brake
- Rope Hooks
- Heavy Duty Heat Treated Hitch Eye



Optional Extras Available include :-

- Hardwood Floor
- Hydraulic Loading Ramps
- Sprung Drawbar
- High Speed Running Gear
- Under-run Bars
- Strap / Rope Box



	8 Tonne		11 Tonne		16 Tonne	
Bed length (flat)	3660mm	12ft	4810mm	15ft 10"	4810mm	15ft 10"
Bed length (inc tail)	4920mm	16ft 2"	6080mm	20ft	6080mm	20ft
Bed width	2500mm	8ft 2"	2500mm	8ft 2"	2500mm	8ft 2"
Floor Thickness (Treadplate)	4.5mm		4.5mm		4.5mm	
Floor Thickness (Hardwood)	25mm	1"	25mm	1"	25mm	1"
Chassis	200 x 75 PFC		230 x 75 PFC		250 x 150 RHS	
Axle (tandem)	70mm 6 stud		80mm 8 stud		90mm 8 stud	
Brake size	300 x 60mm		350 x 60mm		300 x 135mm	
Tyre size	12.5/80 x 15.3 14 ply		340/65R18 radial		Twin 215/75R17.5	
Wheel track	1800mm	6ft	1800mm	6ft	1800mm	6ft
Bed height	1015mm	3ft 4"	995mm	3ft 1"	870mm	2ft 10"
O/a length	6350mm	20ft 10"	7620mm	25ft	7620mm	25ft
O/a width	2500mm	8ft 2"	2500mm	8ft 2"	2500mm	8ft 2"
Unladen weight	2.0 Tonne approx		2.7 Tonne approx		3.0 Tonne approx	

AW Engineering (Hereford) Ltd.
Stoney Street
Madley
Hereford
HR2 9NQ

Tel : 01981 251558
Fax : 01981 251568

Web : www.awtrailers.co.uk
Email : sales@awtrailers.co.uk