AN TRAILERS -

Low Loader Trailers

There are two types of Low Loader Trailers available :-

Standard Low Loader Trailer

The standard Low Loader Trailer has a flat bed with a single axle at the rear which is hydraulically operated so that the bed can be lowered to the ground for easy loading and then raised for travelling. This trailer is designed to transport agricultural implements such as power harrows and drill combinations.

Plant Low Loader Trailer

This has tandem axles under a flat bed with a beaver tail and fold down ramps at the rear for easy loading. It is designed to carry wheeled or tracked plant and equipment including diggers and excavators.





Standard Low Loader Trailer





6 Tonne Low Loader with optional drawbar skid

Standard Low Loader Trailer Features :-

- Hydraulic Brakes
- Full Road Lighting
- Commercial Ratchet type Park Brake
- Rope Hooks
- Heavy Duty Heat Treated Hitch Eye
- Choice of Steel Treadplate or Softwood Floor

Optional Extras Available include :-

- Hardwood Floor
- Drawbar Skid
- Steering Axle

Please turn over for Plant Low

Loader →

5 Tonne, 6 Tonne & 7 Tonne Low Loader

	5 Tonne		6 To	nne	7 Tonne	
Body length	4270mm	14'	5485mm	18'	6400mm	21'
Body width	2500mm	8' 2"	2500mm	8' 2"	2500mm	8' 2"
Chassis	150 x 75 PFC		180 x 7	75 PFC	200 x 75 PFC	
Axle (single)	70mm 6 stud		70mm 6 stud	80mm 8 stud	80mm 8 stud	
Brake size	300 x 60mm		300 x 60mm	350 x 60mm	350 x 60mm	
Tyre size	12.5/80 x 15.3 14 ply		12.5/80 x 15.3 14 ply	385/65R22.5 'super single'	385/65R22.5 'super single'	
Wheel track	2000mm		2000)mm	2000mm	
Lifting rams	2		2	2	2	
o/a length	6585mm	21' 8"	7900mm	25' 11"	9100mm	29' 10"
o/a width	2500mm	8' 2"	2500mm	8' 2"	2500mm	8' 2"



Standard Low Loader Trailer Features :-

- 6mm Steel Tread Plate Floor
- Spring Assisted Loading Ramps
- 18" high Fixed Headboard
- Hydraulic Brakes
- Full Road Lighting
- Commercial Ratchet type Park Brake
- Rope Hooks
- Heavy Duty Heat Treated Hitch Eye



Optional Extras Available include :-

- Hardwood Floor
- Hydraulic Loading Ramps
- Sprung Drawbar
- High Speed Running Gear
- Under-run Bars
- Strap / Rope Box



<u>8 Tonne, 11 Tonne & 16 Tonne Plant Low Loader</u>											
	8 Tonne		11 Tonne		16 Tonne						
Bed length (flat)	3660mm	12'	4810mm	15' 10"	4810mm	15' 10"					
Bed length (inc tail)	4920mm	16' 2"	6080mm	20'	6080mm	20'					
Bed width	2500mm	8' 2"	2500mm	8' 2"	2500mm	8' 2"					
Floor Thickness (treadplate)	4.5mm		4.5mm		4.5mm						
Floor Thickness (hardwood)	25mm	1"	25mm	1"	25mm	1"					
Chassis	200 x 75 PFC		230 x 75 PFC		250 x 150 RHS						
Axle (tandem)	70mm 6 stud		80mm 8 stud		90mm 8 stud						
Brake size	300 x 60mm		350 x 60mm		300 x 135mm						
Tyre size	12.5/80 x 15.3 14 ply		340/65R18 radial		Twin 215/75R17.5						
Wheel track	1800mm	6'	1800mm	6'	1800mm	6'					
Bed height	1015mm	3' 4"	995mm	3' 1"	870mm	2' 10"					
o/a length	6350mm	20' 10"	7620mm	25'	7620mm	25'					
o/a width	2500mm	8' 2"	2500mm	8' 2"	2500mm	8' 2"					
Unladen weight 2.0 Tonne approx		e approx	2.7 Tonne approx		3.0 Tonne approx						